

Xerox® WorkCentre™ 5021

Black-and-white Multifunction System



WorkCentre 5021 Platen	
Speed	
Black and white	Up to 20 ppm (pages per minute) 8.5 x 11 in. / A4 (210 x 297 mm) LEF
First-Page-Out Time	
Copy	As fast as 7.5 seconds
Print	As fast as 14 seconds
Paper Handling	
Platen	
Maximum Scan Area	Up to 11 x 17 in. / 297 x 432 mm
Bypass Tray	
Capacity¹	100 sheets
Sizes	Custom sizes: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3
Weights	16 lb. bond to 30 lb. bond / 60 to 110 gsm
Types	Plain paper Recycled paper Labels
Tray 1	
Capacity¹	250 sheets
Sizes	Standard selectable sizes: 8.5 x 11 in. to 11 x 17 in. / B5 to A3
Weights	16 lb. bond to 24 lb. bond / 60 to 90 gsm
Types	Plain paper Recycled paper

¹ Paper capacities are based on 20 lb. bond / 75 gsm stock; capacities will vary with different weight stocks.

Xerox® WorkCentre™ 5021

Black-and-white Multifunction System

Tray 2 (Optional)	
Capacity ¹	500 sheets
Sizes	Standard selectable sizes: 8.5 x 11 in. to 11 x 17 in. / B5 to A3
Weights	16 lb. bond to 24 lb. bond / 60 to 90 gsm
Types	Plain paper Recycled paper
Paper Capacity	
Standard Capacity ¹	350 sheets
Maximum Capacity ¹	850 sheets
Copy Specifications	
Document Scanner	Platen
Sides (input:output)	1:1, 1:2 and 2:1
Quantity	1 to 999
Resolution	600 x 600 dpi
Concurrency	Concurrent scanning and printing
Copy Features	Reduce/Enlarge N-up ID Card Copy Light/Darken Auto Rotation
Reduction/Enlargement	Variable Zoom from 25% - 400% in 1% increments Six User-Programmable percentages (25%, 64%, 78%, 129%, 154% and 200%)
Print Specifications	
System	
Memory	128 MB
Processor	300 MHz
Page Description Languages	HBPL
Print Resolution	Up to 600 x 600 dpi
Print Features	Watermark Poster N-up Booklet Mixed Document Toner Save
Connectivity	High speed USB 2.0 direct print, optional 10Base-T / 100Base-TX Network Card (not available with network scanning)

¹ Paper capacities are based on 20 lb. bond / 75 gsm stock; capacities will vary with different weight stocks.

Xerox® WorkCentre™ 5021

Black-and-white Multifunction System

Client Operating Systems	Microsoft® Windows® XP (32/64-bit) Windows Server 2003 (32/64-bit) Windows Vista (32/64-bit) Windows Server 2008 (32/64-bit) Windows Server 2008 R2 Windows 7 (32/64-bit) Windows 8 (32/64-bit) - Available post-launch Linux®
Fonts	Postscript 3: 136 Type 1 fonts, 2 Multiple Master fonts PCL: 82 scalable fonts, line printer bitmap font
Printer Drivers	
Operating System	Microsoft® Windows® XP (32/64-bit) Windows Server 2003 (32/64-bit) Windows Vista (32/64-bit) Windows Server 2008 (32/64-bit) Windows Server 2008 R2 Windows 7 (32/64-bit) Windows 8 (32/64-bit) - Available post-launch Linux®
Scan Specifications	
Scanning	
Capability	256 shades, Grey scale or black and white
Concurrency	Scan while the system is printing
Input Speed	Simplex: Scan at 20 ipm black-and-white 216 x 279 mm/A4 (LEF)
Resolution	Up to 600 x 600 dpi
Maximum Scan Area	Platen: A3 / 297 x 432 mm DADF: A3 / 297 x 432 mm
File Formats²	TIFF PDF BMP XDW
Scan Features	Scan to PC Desktop® SE Personal Edition <ul style="list-style-type: none"> • A desktop and server-based offering that provides document imaging, archiving, editing and organization tools • Nuance PaperPort – image viewing and file management software • Nuance OmniPage (for desktop/client installation) – OCR and file format conversion software • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops. Support for Linux Scan (available post-launch)
Supported Scan Destinations	Scan to PC Scan to TWAIN application
Device Specifications	
Accounting	
Tracking	Copy usage
Accounting	Up to 10 User accounts (User ID)

² Dependent on client application software

Xerox® WorkCentre™ 5021

Black-and-white Multifunction System

Monthly Duty Cycle				
	Up to 20,000 pages / month ³			
Recommended Monthly Print Volume				
	Up to 2,500 pages / month ⁴			
Optional Accessories				
	Additional Tray 2 Mobile Stand			
Electrical				
110–127 VAC, 50/60 Hz				
Power Consumption				
Operating (avg.)	511 watts			
Low Power Mode	40 watts			
Ready Mode	65 watts			
Sleep Mode	2.4 watts			
220–240 VAC, 50/60 Hz				
Power Consumption				
Operating (avg.)	478 watts			
Low Power Mode	42 watts			
Ready Mode	56 watts			
Sleep Mode	2.5 watts			
Warm Up	30 seconds (maximum)			
Low-Power Recovery	30 seconds (maximum)			
Required Temperature Range (Storage)	4° to 122° F / -15° to 50° C			
Required Temperature Range (Operating)	50° to 90° F / 10° to 32° C			
Required Relative Humidity	15 to 85 %			
Noise Emission				
Sound Power				
Standby:	3.67 B(A)			
Running:	6.81 B(A)			
Sound Pressure				
Standby:	20 dB(A)			
Running:	52 dB(A)			
Dimensions and Weights	Width	Depth	Height	Weight
Base Unit	23.4 in. / 595 mm	22.4 in. / 569 mm	22.8 in. / 581 mm	79.3 lbs. / 36 kg
Certifications				
	UL-60950-1/CSA-60950-1-07, 2nd Edition CE Mark applicable to Directives 2006/95/EC, 2004/108/EC, 1999/5/EC ENERGY STAR®			

³ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

⁴ Range reflects the number of pages per month the product can regularly print while maintaining optimal performance (considering factors including supplies replenishment and reliability over the expected product life).

Xerox® WorkCentre™ 5021

Black-and-white Multifunction System

Supplies	Description	Order Number
Standard-Capacity Toner Cartridge	9,000 standard pages ⁵	006R01573
Drum Cartridge	80,000 pages ⁶	013R00670
Options	Description	Order Number
Additional Paper Tray	500 sheets	497K11610

⁵ Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.

⁶ Approximate pages. Declared yield based on an LEF A4 job size. Yield will vary based on media size and orientation.

